

AIMTEST™ 73mm



AIMTEST™ 73mm is a simple, robust and effective sub-caliber, in-bore gunnery training system designed, developed and tested for use in the smooth bore 73mm 2A28 Infantry Fighting Vehicle guns.

The Leader in Live-Fire, Sub-Caliber Gunnery Training Systems for the World's Armored Forces

Features & Benefits

- Designed for full-scale, live-fire gunnery training of Infantry Fighting Vehicles (IFV).
- Drastically reduces training ammunition costs. Allows main-gun training on either full-scale or small arms range facilities.
- Simple installation, operation and maintenance ensures efficient crew training.
- Excellent individual and collective sub-caliber gunnery training system for static fire or fire and maneuver training.
- Built-in Anti-Roll System to prevent rotation of the device in the breech.
- Precision Barrel Assembly installs into the main gun chamber.
- Developed on a "Train as you Fight" basis, reducing any negative training.
- Integrated Electrical Harness and Fire Control Integration Box (F.C.I.B.) that connects to and utilizes the vehicle's fire control system.

AIMTEST is fielded in the following countries:

-  Australia
-  Bahrain
-  Belgium
-  Brazil
-  Chile
-  Denmark
-  Egypt
-  Finland
-  Greece
-  Iraq
-  Jordan
-  Morocco
-  Oman
-  Saudi Arabia
-  Spain
-  United Kingdom
-  United States





AIMTEST™ 73mm

AIMTEST 73mm is the cost-effective solution required to “bridge” the training gap between simulators and main gun live-fire training to include urban gunnery training.



AIMTEST™ SYSTEM, 73mm

The Leader in Live-Fire, Sub-Caliber Gunnery Training Systems for the World’s Armored Forces

Detailed Specifications

RANGE:
 Max Effective Range: 1500m with M20 API-T / M17 Tracer
 200m with M860 SRTA

RECEIVER, BOLT and SOLENOID ASSEMBLY:
 Action Type: Bolt Action, Single shot
 Length: 12-3/4 inches / 32.4 cm
 Weight: 17 lbs / 7.7 kgs

BARREL ASSEMBLY:
 Precision machined Barrel & housing adapters Heavy cal. .50 (12.7 X 99mm)
 Length: (w/ flash diverter) 36 inches / 91.4 cm
 Weight: 30 lbs / 13.6 kgs

FIRING ASSEMBLY:
 Rate of Fire: Single shot
 Firing Assy Connectivity: Vehicle’s existing firing circuit
 Firing Mechanism: Manual, electrically actuated solenoid

SOLENOID ASSEMBLY:
 Operational Voltage Range: 24 VDC (18-32 VDC)
 Operational Temperature: -40 - +125 degrees Fahrenheit
 -40 - +52 degrees Celsius
 Operational Force: 52 daN (116 lbs.) - Maximum
 45 daN (100 lbs.) – Normal

SAFETY: Utilizes Main Gun Safety System



- Excellent individual and collective gunnery training device for full, scaled and urban ranges.
- Environmentally friendly with small noise signature and reduced range requirements.
- Rapidly and easily installed in approx. 10 minutes, saving valuable range time.
- Fires any NATO standard cal. .50 ammunition.
- A “Train as you Fight” device requiring little initial training to operate.
- Uses vehicle’s own Fire Control System without harm to Fire Control components.
- Easily maintained and deployed at unit level.



American Apex Corporation
 105 Innovation Ct., Suite I
 Delaware, OH USA 43015
 (614) 652-2000
 (614) 652-2001 Fax
 www.americanapex.com
 www.gunnerytraining.com
 info@americanapex.com